

05/23/00

Please type a plus sign (+) inside this box → ☐

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

PTO/SB/05 (2/98)

Approved for use through 09/30/2000. OMB 0651-0032

Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 C.F.R. § 1.53(b))

Attorney Docket No. 12,103

First Inventor or Application Identifier John M. Savage Jr.

Title LENS UNIT AND FIBER OPTIC CABLE ASSEMBLY

Express Mail Label No.

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

1. ☒ * Fee Transmittal Form (e.g., PTO/SB/17)
(Submit an original and a duplicate for fee processing)
2. ☒ Specification [Total Pages 22]
(preferred arrangement set forth below)
- Descriptive title of the invention
 - Cross References to Related Applications
 - Statement Regarding Fed sponsored R & D
 - Reference to Microfiche Appendix
 - Background of the invention
 - Brief Summary of the invention
 - Brief Description of the Drawings (if filed)
 - Detailed Description
 - Claim(s)
 - Abstract of the Disclosure
3. ☒ Drawing(s) (35 U.S.C. 113) [Total Sheets 3]
4. Oath or Declaration [Total Pages 2]
- a. ☒ Newly executed (original or copy)
 - b. ☐ Copy from a prior application (37 C.F.R. § 1.63(d))
(For continuation/divisional with Box 17 completed)
(Note Box 5 below)
 - i. ☐ DELETION OF INVENTOR(S)
Signed statement attached deleting inventor(s) named in the prior application, see 37 C.F.R. §§ 1.63(d)(2) and 1.33(b).
5. ☐ Incorporation By Reference (useable if Box 4b is checked)
The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered to be part of the disclosure of the accompanying application and is hereby incorporated by reference therein.

ADDRESS TO: Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

6. ☐ Microfiche Computer Program (Appendix)
7. Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)
- a. ☐ Computer Readable Copy
 - b. ☐ Paper Copy (identical to computer copy)
 - c. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

8. ☐ Assignment Papers (cover sheet & document(s))
9. ☐ 37 C.F.R. § 3.73(b) Statement (when there is an assignee) ☐ Power of Attorney
10. ☐ English Translation Document (if applicable)
11. ☒ Information Disclosure Statement (IDS)/PTO-1449 ☐ Copies of IDS Citations
12. ☐ Preliminary Amendment
13. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
14. ☒ * Small Entity Statement(s) ☐ Statement filed in prior application, Status still proper and desired (PTO/SB/08-12)
15. ☐ Certified Copy of Priority Document(s) (if foreign priority is claimed)
16. ☐ Other:

* NOTE FOR ITEMS 1 & 14: IN ORDER TO BE ENTITLED TO PAY SMALL ENTITY FEES, A SMALL ENTITY STATEMENT IS REQUIRED (37 C.F.R. § 1.17), EXCEPT IF ONE FILED IN A PRIOR APPLICATION IS RELIED UPON (37 C.F.R. § 1.30).

17. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No: _____

Prior application information: Examiner _____ Group / Art Unit _____

18. CORRESPONDENCE ADDRESS

☐ Customer Number or Bar Code Label

or ☒ Correspondence address below

(Insert Customer No. or Attach bar code label here)

Name Mr. William W. Haefliger

Address 201 S. Lake Ave., Suite 512

City Pasadena

State

CA

Zip Code

91101

Country USA

Telephone

323 684-2707

Fax

626 449-0520

Name (Print/Type)

William W. Haefliger

Registration No. (Attorney/Agent)

17,120

Signature

Date

May 17, 2000

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

**STATEMENT CLAIMING SMALL ENTITY STATUS
(37 CFR 1.9(f) & 1.27(b))--INDEPENDENT INVENTOR**

Docket Number (Optional)

12,103

Applicant, Patentee, or Identifier: John M. Savage, Jr.

Application or Patent No.: _____

Filed or Issued: _____

Title: LENS UNIT AND FIBER OPTIC CABLE ASSEMBLY

As a below named inventor, I hereby state that I qualify as an independent inventor as defined in 37 CFR 1.9(c) for purposes of paying reduced fees to the Patent and Trademark Office described in:

- ☒ the specification filed herewith with title as listed above.
☐ the application identified above.
☐ the patent identified above.

I have not assigned, granted, conveyed, or licensed, and am under no obligation under contract or law to assign, grant, convey, or license, any rights in the invention to any person who would not qualify as an independent inventor under 37 CFR 1.9(c) if that person had made the invention; or to any concern which would not qualify as a small business concern under 37 CFR 1.9(d) or a nonprofit organization under 37 CFR 1.9(e);

Each person, concern, or organization to which I have assigned, granted, conveyed, or licensed or am under an obligation under contract or law to assign, grant, convey, or license any rights in the invention is listed below:

- ☒ No such person, concern, or organization exists.
☐ Each such person, concern, or organization is listed below.

Separate statements are required from each named person, concern, or organization having rights to the invention stating their status as small entities: (37 CFR 1.27)

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate: (37 CFR 1.28(b));

John M. Savage, Jr.

NAME OF INVENTOR

NAME OF INVENTOR

NAME OF INVENTOR

Signature of inventor

Signature of inventor

Signature of inventor

Date

Date

Date

TO ALL WHOM IT MAY CONCERN:

5 BE IT KNOWN THAT I, JOHN M. SAVAGE, JR.,
a citizen of the United States of America, residing
in Solana Beach, in the County of San Diego, State
of California, have invented a new and useful
improvement in

10

LENS UNIT AND FIBER OPTIC CABLE ASSEMBLY

15

BACKGROUND OF THE INVENTION

5 This invention relates generally to optical coupling of light sources and fiber optics cables, or light pipes; and more particularly concerns optical coupling of lens units and light fibers in such a way as to position the cable to receive light transmission from a light source spaced endwise from the light source, such as an LED.

10 There is need for improved apparatus and method to overcome difficulties in optical coupling as between light sources, light pipes and lenses.

SUMMARY OF THE INVENTION

15 It is a major object of the invention to provide improvements in such optical coupling as will meet the referenced need. Basically a light transmission device in accordance with the invention comprises:

20 a) a fiber optics cable having light entrance and light exit ends,

b) structure including a body receiving the entrance end of the light pipe for positioning the entrance the to receive light,

c) the structure including a receiver in the body,

d) and at least one anchor carried by the structure to a mounting board, for positively positioning the structure, body and receiver, relative to the board.

It is another important object to provide a portion of the structure to be sidewardly offset relative to the receiver, the one anchor being in substantial alignment with the portion of the structure, and there being a shoulder on said one portion of the structure in substantial alignment with the anchor to receive pushing force transmission from a tool to drive the anchor toward an opening in said board.

Another object is to provide a tool receiving recess in said structure, the shoulder being associated with that recess.

A further object is to provide a light focusing and transmitting lens located in the

structure in alignment with the entrance end of the light pipe.

In this regard the lens and receiver are preferably unitary, for simplicity; and the light source is preferably in the form of an LED located in a cavity in the body, in alignment with the receiver.

Yet another object is to provide multiple of the anchors projecting from a mounting surface defined by said structure, the anchors offset from an axis defined by the receiver, totally support the structure.

An additional object is to provide the body to have multiple sides, two of which form tongue and groove configurations to receive corresponding groove and tongue elements of adjacently mounted bodies.

Yet another is to provide a lens unit at the light exit end of the cable; the lens unit preferably having a light transmitting end wall, and a side wall extending away from that end wall, the cable light exit end retained in assembled relation to that side wall, whereby light is transmitted from the cable exit end to said lens unit end wall.

5 A yet additional object includes provision of a tubular retainer receiving the light exit end of the cable, the tubular retainer assembled to the lens unit side wall. That side wall preferably has multiple spring fingers, and said retainer and fingers have interlocking relation. The retainer and fingers typically have tongue and groove interlocking relation. As will be seen, the retainer preferably has an exterior flange or ring, and at least one of said fingers has a groove receiving at least part of the flange.

Further, the spring fingers preferably have cam surfaces thereon to be spread apart in response to axial movement of the retainer relative to the spring fingers.

A yet further object includes a support panel carrying said LED, and another support panel supporting said lens unit said panels spaced apart in fixed relation.

20 An additional object is to provide:

- a) a fiber optics cable having light entrance and light exit ends,
- b) a lens unit at the light exit end of the cable, said unit having a light transmitting

end wall, a side wall extending away from said end wall, the cable light exit end retained in assembled relation to said side wall, whereby light is transmitted from the cable exit end to said lens unit end wall,

c) and a tubular retainer receiving said light exit end of the cable, to position the cable exit end relative to the unit end wall whereby that end wall is substantially fully illuminated by light from the cable, the tubular retainer assembled to said side wall.

As will be seen, the side wall and cable (or light pipe) exit end may have interlocking relation; the side wall may provide multiple retention fingers; the retainer may have an exterior flange, and at least one of the finger may have a groove receiving at least part of the flange; and the fingers may have cam surfaces to be deflected in response to axial movement of the retainer relative to the fingers. Also, the retainer position the cable exit end relative to the lens unit end wall, whereby that end wall is substantially fully illuminated by light from the cable exit end.

Further objects include provision of a light focusing and transmitting lens located in said structure in alignment with said entrance end of the light pipe; the lens having a substantially flat light exit surface to align with the cable core; the cable having a plastic jacket surrounding said core, said jacket retained to a bore defined by the receiver; and cable retention elements on the receiver that carries the lens and receives the cable entrance end.

These and other objects and advantages of the invention, as well as the details of an illustrative embodiment, will be more fully understood from the following specification and drawings, in which:

DRAWING DESCRIPTION

Fig. 1 is a section taken in elevation to show elements of the invention;

Fig. 2 is an exploded side view of elements of the invention;

Fig. 3 is an end view taken on lines 3-3 of Fig. 2; and

Fig. 4 is an exploded view of structure at the light entrance end of the cable.

5

DETAILED DESCRIPTION

In Fig. 1, an optical pipe cable 10 has opposite ends 11 and 12. End 11 is endwise received leftwardly into a tubular retainer 50 which is in turn received into a lens unit 13 to be fixedly positioned coaxially relative to that unit. The lens unit has a light transmitting end wall 14, or lens, and a skirt 15 integral with that end wall and extending axially rightwardly. The end 11 of the pipe 10 directly faces 14, which has facets 14a on the end wall interior face to receive and diffuse light transmitted axially by the cable. Note the leftwardly convex outer surface 14b of the lens wall 14, to transmit light as in divergent directions as indicated.

The lens unit skirt 15 has structure extending away from end wall 14 generally axially rightwardly, and sidewardly of the retainer side

5 wall 50a. That structure may be considered as including retention structure, as in the form of like retention fingers 50b (which may be spring fingers) spaced about the axis 21. Four such fingers may be provided. Those fingers have leftward ends 50c integral with and projecting rightwardly from skirt 15, as shown, and rightward ends to be yieldably resiliently spread apart as the retainer is assembled leftwardly into the lens unit, facilitating ready intercoupling of the cable 10 and lens unit 13, in intercoupled relation, as for example in tongue and groove snap fit relation, precisely coaxially positioning these elements. The cable left end portion fits into the bore 50c of 50, as by an interference fit, for retention. The rightward end of bore 50c may be slightly flared for ease of reception of the cable and portion. A retainer shoulder 50d stops the left end of the cable. Accordingly, the cable light exit end is positioned relative to end wall 14 to direct exiting light to substantially fully illuminate wall 14. Light may diverge or flare between the cable end and wall 14, to achieve such illumination.

As shown, the retainer has an integral exterior flange 23 in the form of a ring extending about axis 21, and the fingers have grooves 26 into which the flange is received upon assembly. The groove lengths match the flange length, so that the cable is held in coaxial relation to the lens unit. In that position the flared bore 50e of the retainer passes light to all, or substantially all, the facets 14a.

Longitudinally extending gaps are typically formed circumferentially between successive spring fingers, and a protrusion may be provided on the flange 23 to extend radially outwardly into one of such gaps. Its sideward engagement with one of the fingers blocks relative rotation of the cable and lens unit, about axis 21. The fingers have cam surfaces thereon to be spread apart upon relative axial movement of the pipe relative to the fingers. As shown there are certain cam surfaces 30 that are divergent in a direction away from the lens unit end wall 14; and there are other cam surfaces 31 that are convergent in a direction toward the lens unit end wall. Surfaces 30 are spread apart as the retainer is

pushed endwise into the lens unit, and surfaces 31 are spread apart when the retainer is displaced endwise away from the lens unit 13.

5 Figs. 1 and 4 also show a light source such as LED 34 spaced axially from the end 12b of the cable, and directed toward that end. Accordingly, when LED 34 is "ON", light is transmitted to and through the cable, and through the end wall 14 of lens unit 13.

0 Structure 35, including a body 36, receives the light entrance end 12e of the cable 10, for positioning that entrance end to receive light. Body 36 has a bore 36a into which the light entrance end of the cable is received, for 5 positioning that entrance end to receive light from the LED. Structure 35 preferably also includes a receiver 38 received in body bore 36a, as shown. The receiver has a sleeve portion 38a defining a bore 38b into which the cable end is received and 20 retained, as for example by an interference fit, or by a bonding layer.

A light transmitting lens 40 is located, in the structure 35 in axial alignment with the LED and with the light entrance end 12b of the cable.

A light transmitting lens 40 is located, in the structure 35 in axial alignment with the LED and with the light entrance end 12b of the cable. Lens 40 may consist of synthetic resin, and be molded integrally with the receiver 38. That lens has a light entrance end 40a that is convex toward the LED 34, and a light discharge end 40b that is flat to flatly engage and position or stop the end 12b of the cable. The lens acts as a focusing lens to efficiently gather and transmit light from the LED to direct it axially into the central or core portion 12c of the cable containing light transmitting fibers. That core portion is surrounded by a plastic jacket 12d which may be heat bonded to the bore of the plastic receiver 38. The receiver 38 may advantageously have a sleeve portion 38a defining cantilevered spring fingers 38b separated by a slot or slots 38c, and convex protrusions 38d that engage the jacket 12d, to assist in cable retention. Ribs 42 on the body bore 36a frictionally engage the outer surface of sleeve portion 38a to aid in retaining it in position.

At least one anchor carried by the body 36 attaches to a mounting board, for positively positioning said structure, said body and receiver, relative to the board. See for example pin 60 projecting downwardly from the flat lower surface 35a of the structure 35, to penetrate through a locating opening 62 in board 63. Ribs 60a on pin 60 frictionally retain it to opening 62. Pins or pegs 60 can be heat staked to the PCB 63.

A portion 36b of body 36 of structure 35 is sidewardly offset relative to the receiver, said one anchor 60 being in alignment with said portion 36b of the body. A shoulder 65 on said portion 36b of said structure is in alignment with the anchor pin to receive pushing force transmission from a tool indicated at 70 to drive said anchor toward opening 62 in board 63.

A tool receiving recess 54 is formed in the upper portion of body portion 36b, and the shoulder 65 is associated with recess 54. Typically the shoulder may be located internally of 54b.

Preferably, multiple of such anchors may be provided, projecting from a mounting surface

three-point stability when they fit in the openings provided in panel 35.

5 Finally, body 36 has block shape, and has multiple sides, two of said sides forming tongue and groove configurations to receive corresponding groove and tongue elements of adjacently mounted bodies. See for example dove-tailed tongue 80 on the body side, and dove-tailed groove 81 on the opposite body side. Cut-out 83 in the body 36 is adapted to receive the LED 34, and structure 34a associated with the LED.

10 Accordingly, a very simple effective apparatus is provided for stably supporting opposite ends of a fiber optics cable, in end abutting and aligning relation to the cable, for 15 light transmission. Ready connection and disconnection of the cable opposite ends to and from the board 63 and to and from the lens unit 13, are afforded.

I CLAIM:

1. A device for transmitting light, comprising, in combination,

a) a fiber optics cable having light entrance and light exit ends,

b) structure including a body for positioning said entrance end to receive light,

c) said structure including a receiver carried by the body and receiving the entrance end of the cable,

d) and at least one anchor carried by said structure to attach the structure to a mounting board, for positively positioning said structure, and said body and receiver, relative to the board.

2. The combination of claim 1 wherein a portion of said structure is sidewardly offset relative to the receiver, said one anchor being in substantial alignment with said portion of said structure, and there being a shoulder on said one portion of said structure in substantial alignment with said anchor to receive pushing force transmission from a tool to drive the anchor toward an opening in the board.

3. The combination of claim 2 wherein there is a tool receiving recess in said structure, said shoulder being associated with said recess.

4. The combination of claim 1 including a light focusing and transmitting lens located in said structure in alignment with said entrance end of the light pipe.

5. The combination of claim 4 wherein said lens is associated with said receiver and the cable has a light transmitting core in alignment with a substantially flat light transmitting surface of the lens.

6. The combination of claim 5 wherein the lens and receiver are unitary, and the cable has a plastic jacket surrounding said core, said jacket retained to a bore defined by the receiver.

7. The combination of claim 6 including a cavity in the receiver in alignment with said lens for receiving a light source.

8. The combination of claim 7 including said light source in the form of an LED, in said cavity.

9. The combination of claim 1 wherein there are multiple of said anchors projecting from a mounting surface defined by said structure, said anchors offset from an axis defined by the receiver.

10. The combination of claim 9 wherein there are three of said anchors.

11. The combination of claim 1 wherein said body has multiple sides, two of said sides forming tongue and groove configurations to receive corresponding groove and tongue elements of adjacently mounted bodies.

12. The combination of claim 1 including a lens unit at the light exit end of the cable.

13. The combination of claim 12 wherein said lens unit has a light transmitting end wall, a side wall extending away from said end wall, the cable light exit end retained in assembled relation to said side wall, whereby light is transmitted from the cable exit end to said lens unit end wall.

14. The combination of claim 13 including a tubular retainer receiving said light exit end of the cable, the tubular retainer assembled to said side wall.

15. The combination of claim 14 wherein said side wall and said cable light exit end have interlocking relation.

16. The combination of claim 14 wherein said side wall has multiple spring fingers, and said retainer and fingers have interlocking relation.

17. The combination of claim 16 wherein said retainer and fingers have tongue and groove interlocking relation.

18. The combination of claim 16 wherein said retainer has an exterior flange, and at least one of said fingers has a groove receiving at least part of said flange.

19. The combination of claim 13 wherein said end wall has an inner face directed axially toward said cable light exit end, said inner face having facets.

20. The combination of claim 16 wherein said spring fingers have cam surfaces thereon to be spread apart in response to axial movement of the retainer relative to the spring fingers.

21. The combination of claim 20 wherein said cam surfaces are divergent in a direction away from said lens unit end wall.

22. The combination of claim 20 wherein said cam surfaces are convergent in a direction away from said lens unit end wall.

23. The combination of claim 16 wherein the retainer has a substantially cylindrical side surface in closely spaced relation to said spring fingers.

24. The combination of claim 12 including a panel carrying said lens unit.

25. The combination of claim 12 wherein said cable light entrance end is spaced from said unit end wall, and including an LED facing and spaced from said cable light entrance end to transmit light into the cable via said entrance end.

26. A device for transmitting light, comprising,
in combination,

a) a fiber optics cable having light entrance
and light exit ends,

b) a lens unit at the light exit end of the
cable, said unit having a light transmitting end wall, a
side wall extending away from said end wall, the cable light
exit end retained in assembled relation to said side wall,
whereby light is transmitted from the cable exit end to said
lens unit end wall,

c) and a tubular retainer receiving said light
exit end of the cable, to position the cable exit end
relative to the unit end wall whereby that end wall is
substantially fully illuminated by light from the cable, the
tubular retainer assembled to said side wall.

27. The combination of claim 26 wherein said side
wall and said cable light exit end have interlocking
relation.

28. The combination of claim 26 wherein said side
wall has multiple retention fingers, and said retainer and
fingers have interlocking relation.

29. The combination of claim 27 wherein said retainer has an exterior flange, and at least one of said fingers has a groove receiving at least part of said flange.

30. The combination of claim 26 wherein said end wall has an inner face directed axially toward said cable light exit end, said inner face having facets.

31. The combination of claim 28 wherein said fingers have cam surfaces thereon to be spread apart in response to axial movement of the retainer relative to the fingers.

32. The combination of claim 31 wherein said cam surfaces are divergent in a direction away from said lens unit end wall.

33. The combination of claim 31 wherein said cam surfaces are convergent in a direction away from said lens unit end wall.

34. The combination of claim 28 wherein the retainer has a substantially cylindrical side surface in closely spaced relation to said spring fingers.

35. The combination of claim 26 including a panel carrying said lens unit.

36. The combination of claim 12 wherein said cable light entrance end is spaced from said unit, and including an LED facing and spaced from said cable light entrance end to transmit light into the cable via said entrance end.

37. The combination of claim 36 including a support board carrying said LED, and another support panel supporting said lens unit, said panels spaced apart in fixed relation.



38. The combination of claim 1 including a bore defined by the body, the receiver extending in said bore and retained to said bore.

39. The combination of claim 38 including retention ribs on one of said bore and receiver.

ABSTRACT OF THE DISCLOSURE

A device for transmitting light, comprising, in combination, a fiber optics cable having light entrance and light exit ends, structure including a body receiving the entrance end of the light pipe for positioning said entrance end to receive light, said structure including a receiver in the body, and at least one anchor carried by said structure to attach the structure to a mounting board, for positively positioning said structure, and said body and receiver, relative to the board.

Original



147

Please type a plus sign (+) inside this box → +

PTO/SB/01 (12-97)

Approved for use through 9/30/00. OMB 0651-0032
Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

DECLARATION FOR UTILITY OR DESIGN PATENT APPLICATION (37 CFR 1.63) <input checked="" type="checkbox"/> Declaration Submitted with Initial Filing OR <input type="checkbox"/> Declaration Submitted after Initial Filing (surcharge (37 CFR 1.16 (e)) required)	Attorney Docket Number	12,103
	First Named Inventor	John M. Savage, Jr.
	COMPLETE IF KNOWN	
	Application Number	/
	Filing Date	
	Group Art Unit	
	Examiner Name	

As a below named inventor, I hereby declare that:

My residence, post office address, and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

LENS UNIT AND FIBER OPTIC CABLE ASSEMBLY

the specification of which (Title of the Invention)
☒ is attached hereto
OR
☐ was filed on (MM/DD/YYYY) as United States Application Number or PCT International Application Number and was amended on (MM/DD/YYYY) (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment specifically referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56.

I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or of any PCT international application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application Number(s)	Country	Foreign Filing Date (MM/DD/YYYY)	Priority Not Claimed	Certified Copy Attached?	
				YES	NO
			<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>

☐ Additional foreign application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto:

I hereby claim the benefit under 35 U.S.C. 119(e) of any United States provisional application(s) listed below.

Application Number(s)	Filing Date (MM/DD/YYYY)

☐ Additional provisional application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.

[Page 1 of 2]

Burden Hour Statement: This form is estimated to take 0.4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

Please type a plus sign (+) inside this box → ☐

PTO/SB/01 (12-97)

Approved for use through 9/30/00. OMB 0651-0032
Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

DECLARATION — Utility or Design Patent Application

I hereby claim the benefit under 35 U.S.C. 120 of any United States application(s), or 365(c) of any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

U.S. Parent Application or PCT Parent Number	Parent Filing Date (MM/DD/YYYY)	Parent Patent Number (if applicable)

☐ Additional U.S. or PCT international application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.

As a named inventor, I hereby appoint the following registered practitioner(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

☐ Customer Number

OR

☒ Registered practitioner(s) name/registration number listed below

Place Customer
Number Bar Code
Label here

Name	Registration Number	Name	Registration Number
William W. Haeffliger	17,120		

☐ Additional registered practitioner(s) named on supplemental Registered Practitioner Information sheet PTO/SB/02C attached hereto.

Direct all correspondence to: ☐ Customer Number or Bar Code Label


OR ☒ Correspondence address below

Name	Mr. William W. Haeffliger				
Address	201 S. Lake Ave., Suite 512				
Address					
City	Pasadena	State	CA	ZIP	91101
Country	USA	Telephone	323 684-2707	Fax	626 449-0520

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. 1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.


Name of Sole or First Inventor:

☐ A petition has been filed for this unsigned inventor

Given Name (first and middle [if any])		Family Name or Surname	
John M.		Savage, Jr.	
Inventor's Signature			Date
Residence: City	Solana Beach	State	CA
		Country	Sasn Diego
Citizenship	USA		
Post Office Address	538 B. Via De La Valle		
Post Office Address			
City	Solana Beach	State	CA
		ZIP	92075
		Country	USA

☐ Additional inventors are being named on the _____ supplemental Additional Inventor(s) sheet(s) PTO/SB/02A attached hereto

United States Patent & Trademark Office
Office of Initial Patent Examination -- Scanning Division



Application deficiencies were found during scanning:

☒ Page(s) 2 of Drawings were not present
for scanning. (Document title)

☐ Page(s) _____ of _____ were not present
for scanning. (Document title)

☐ Scanned copy is best available